

Construct wrap

general ht

Construct Wrap **general ht** is a high-quality interior water-based, peelable coating specifically designed for the protection of non-porous substrates during the construction phase. Construct Wrap **general ht** has been developed for high temperature and high humidity climates of 18°-40°. Construct Wrap **general ht** has very high scratch and impact resistance, designed to withstand foot traffic scuffing and acting as a permanent 'drop sheet'. Protecting vitrified, ceramic and granite tiles with sealed grout, sealed concrete and timber, glass, stainless steel, 2-pac finishes and porcelain to name a few. Construct Wrap **general ht** diminishes contamination against foreign materials and also offers anti-slip properties for workplace safety.

Step 1

Apply Construct Wrap **general ht** to a dry, dust free clean non-porous substrate using a 12mm nap roller ensuring the coating is thick and even. Use masking tape as a temporary border. Always trial patch first



Step 2

Apply the second coat once the first coat has dried completely. Avoid traffic on uncured product until both coats are fully cured.



Step 3

Peel Construct Wrap **general ht** from the substrate starting at one corner. Remove any remains without marking the substrate and use water if required.



- Replaces crude or ineffective liner materials
- Once cured, it provides an extremely tough, uniform film thickness that is easily removed.
- Peels off in sheets, eliminating messy hand scraping
- Can be applied in multiple coats for heavy traffic areas or added protection
- Offers impact resistance
- Water based for safe use
- Low fumes for application



Contact:

Manufacturer: Skudo Coatings Pty Ltd
 PO Box 148 Robina Queensland 4226 Australia
 Ph: 1300 795 997 Fax: 07 5537 9429